

FOLIANT MERCURY 530 NG

The FOLIANT Mercury 530 NG is a next generation of popular SF version. It is very compact industrial laminating machine, constructed for a heavy duty digital and offset outputs lamination. It is equipped with an integrated suction feeder Heidelberg and a high speed bump separator. Several options are available for the Mercury machine – Foliant Foiler, non-sticky pressure roller, pallet staker, etc. Due to its high pressure system, format and performance the machine is suitable for all jobs – all kinds of digital printed sheets lamination and high volumes of offset printed sheets size B2+ lamination too. **The machine maximum speed is up to 27 m/min.**, while performance is 2300 sheets per hour of B2 portrait (white paper 200 gsm).



FEEDER

The FOLIANT Mercury 530 NG is equipped with a rising pile back separation stream feeder and with a suction feed head Heidelberg. It is driven by an Omron servo motor and controlled by a machine central PLC. The Becker vacuum pump is used for sheets back airing. The overlaps are electronically controlled, in an „in-run“ automatic mode, from the touch screen. The accuracy is +/- 2 mm under-lap (in a constant speed). The feeder is fitted with a lifting plate and its capacity is a 54 cm pile of paper.

LAMINATOR

The FOLIANT Mercury 530 NG laminator maximum sheet size is 53 x 75 cm. The minimum sheet size is 30 x 20 cm (A4). The FOLIANT Mercury 530 NG machine is a single sided thermal industrial laminator, laminating the 115 – 600 gsm paper.

The laminating unit is equipped with an adjustable twin decurl unit:

- With a decurl blade for offset printed sheets decurling
- With a decurl roller for digital printed sheets decurling (to prevent the scratches on sheets printed on both sides by digital print with sensitive inks).

The roll of a film is mounted on a quick-changed shaft with a film tension control breaker. The shaft capacity is up to 3000 m of the 24 - 31 microns film. The film holder unit is equipped with a trim slitter and a perforating wheel.

The laminating process is made between two laminating rollers - a highly polished chrome roller, and a lower hard rubber pressure roller. The laminating roller is heated with a dry electric system inside the roller, with a sensitive temperature sensor. The warming up time is shorter than 10 minutes. The pressure is pneumatically adjustable, with an extra independent control knob for each roller edge.

The machine is fitted with OMRON Programmable Logic Controllers, which control all machines' functions. The used PLC system includes many automation items for an easy control of the machine and a reliable lamination. The whole machine is controlled by an interactive easy understandable icon touch screen panel – no language version is needed.

SEPARATOR

The integrated bump separator (sheeter) is equipped with a pair of fast cycling rollers. The process is controlled from the machine PLC unit. The separated sheets are delivered into a vibrating jogger (optional) or a pallet stacker (optional).

LAMINATING FILMS

The machine laminates the BOPP films (23 – 42 microns) and Nylon films (max. 35 microns). The PET films (max. 25 microns) can be laminated with the optional module only.

OPTIONS

JOGGER 530 (OPTIONAL)

It is an adjustable vibrating reception unit for the laminated sheets stocking. Its capacity is limited up to a 10 cm pile of sheets.

PALLET STACKER - MANUAL (OPTIONAL)*

It is a device equipped with a pallet trolley, pneumatically controlled from the machine PLC, which loads the laminated sheets into a high pile on pallet. Its capacity is 65 cm pile of sheets. Movement up is done manually.

PALLET STACKER – INTEGRATED AUTOMATIC (OPTIONAL)*

Fully automatic device that unloads laminated sheets into a high pile on pallet. Its capacity is 73 cm of paper.

NON-STICKY PRESSURE ROLLER (OPTIONAL)

Standard rubber pressure roller is replaced by roller with non-sticky surface. Melted glue from film cannot stick to it even under heavy pressure. Cleaning of this roller is not necessary at all. Allows laminating sheets with windows.

FOLIANT FOILER (OPTIONAL)

Winding device that allows use of metalized film (gold, silver, red, etc.) and spot varnish film.

FILM MICRO ADJUSTABLE AIR SHAFT (OPTIONAL)

Air shaft for precise and easy film placement.

MODULE FOR SHEETS 53 x 100 CM LAMINATION (OPTIONAL)

It is an extension for lamination of sheets with size up to 53 x 100 cm. Sheets above 75cm cannot be unloaded to Integrated pallet stacker.

PET FILMS LAMINATION MODULE (OPTIONAL)

It is a module integrated inside the separator for the PET films (max. 25 microns) processing.

FILM LOADER/MANIPULATOR (OPTIONAL)

It is an electric lift with a film core adaptor for loading heavy rolls of film (max. capacity 125 kg). The device is not integrated with the machine. It is only connected with the machine electric circuits.



Optional Pallet Stacker (manual)



Optional Pallet Stacker (integrated)



Optional Foliant Foiler

Foliant Mercury 530 NG

Max Speed	27 m / min	Temperature Control	80 - 140°C
Feeding	Automatic	Power Supply	3 ph., 400 V AC, 50-60 Hz
Feeding System	Suction Feeding Head Heidelberg	Power	6000 W
Feeder`s Load Capacity	54 cm	Floor space (w x l) incl. a Jogger	120 x 270 cm
Overlaps	Automatic, PLC Control	Weight	500 kg
Overlaps Accuracy	+ / - 2 mm	Module for PET Films Processing	Optional
Separation	Automatic, Bump Rollers	Foliant Foiler	Optional
Paper Weight	115 - 600 gsm	XL Module (sheets 53 x 100 cm)	Optional
Main Rollers Pressure	Pneumatic	Jogger 530	Optional
External Compressor	150 l / min, 6 - 8 bar	Pallet Stacker Manual	Optional
Min. Sheets Size (w x l)	20 x 30 cm	Pallet Stacker Integrated	Optional
Max. Sheets (w x l)	53 x 75 cm	Non-sticky pressure roller	Optional
Max. Performance	2300 B2 / hour	Film Loader (Electric)	Optional
Warming up Time	8 min	Film Micro Adjustable Air Shaft	Optional